



Dolphin-M2

The application area of the Dolphin-M2 crawler ranges from DN150 upwards





Technical Specification

Tractor	Deployment range	from DN150 upwards
	Steerable	yes
	Drive	6-wheel driven
	Inclination sensor	yes
	Temperature sensor	yes
	Pressure sensor	yes
	Overturn protection	yes
	Back-eye camera resolution	full HD; 2.1 Megapixels; 1920x1080P
	Rear illumination	2 LED
	Protection class	IP68, up to 10m water depth
	Ambient temperature range	-10 ~ 55 °C
	Wheel sets	3inch, 4inch, 5inch, 6inch
	Dimension	L571xW226xH426mm (6-inch wheel set, full elevator)
	Weight	18kg (6-inch wheel set)
Camera	Pan & Tilt	360° endless rotation, 150° panning range
	Camera resolution	full HD; 2.1 Megapixels; 1920x1080P; PAL
	Illumination	4 LED
	Auxiliary light	12 LED
	Elevator	motorized
	Function	defog
	Sensitive to light	> 1Lux
Cable drum	Drive	motor-driven
	Cable length	200m
	Cable tension	250kg
	Winding aid	yes
	Meter counter	±1% accuracy, min. scale: 1cm
	Power	Battery, 10h; power cord (optional)
	Battery	lithium iron phosphate battery, 48v/15ah
	Communication	Wi-Fi connection to control pad
	Protection class	IP65
	Dimension & weight	710x390x480mm, 41kg
Control pad	OS	Android
	Display	10.1 inch
	Storage	64G
	Battery	8h
	Size & weight	102x153x63mm, 280g
	Communication	Bluetooth 6m
	Display information	date, time, tractor position angle, inclination, distance, inspection video, text input, overturn alert and tractor control